

TI175|TI395

Thermal Imaging Cameras for Electricity & Industry Application

ULIRVISION TI175|TI395 are affordable, easy-to-operate and high-performance thermal imaging cameras that offer accurate temperature measurements at safe distances.

TI175|TI395 have a wide range of temperature measurements to satisfy a variety of thermograph applications. They are special electricity and industry applications.

Features

Excellent thermal image and high accuracy temperature measurement

3.2", 270° rotatable and foldable LCD

Multi-mode for temp. measurement, max./min./avg temp, auto tracking, isotherms analysis

Tiny size, light weight 400g

Multi-lens for option

Fusion and overlay of the thermal image & visible image



Applications

Building Diagnostics

Electrical/Mechanical Inspection

Research & Development

Automation Applications

Preventative & Predictive

Maintenance

ULIRVISION

Technical Specifications

Item	TI175	TI395
Detector Data		
Type	Uncooled FPA	
IR resolution	160×120	384×288
Pixel pitch	17μm	
Spectral range	7.5~14μm	
NETD/Sensitivity	70mK	
Lens		
FOV	24°×18°	24°×18°
IFOV	2.6mrad	1.13mrad
Focus	Auto/Motor	
Lens(Optional)	12°×9°	48°×37°/12°×9°/6.0°×4.5°
Image Performance		
Display	3.2", 270° tiltable LCD, 800×480 pixels	
Visual camera	3.0 mega pixel	
Frequency	50Hz/60Hz	
Zoom	1X~4X continuous	1X~8X continuous
Color palettes	12 palettes(including iron, rainbow, white hot and black hot etc.)	
Brightness	Manual	
Measurement		
Temperature range	-20°C ~ +250°C (Standard) +200°C ~ +600°C (Optional)	
Measurement accuracy	±2°C/±2%(reading)	
Spotmeter	4 adjustable spots	
Line profile	1 Vertical/Horizontal	
Area	5 movable areas (rectangular and circular max temp, min temp capture, average temp measurement)	
Isotherms analysis	Capture high/low temperature/interval	
Alarm	Voice, color	
Measurement correction	Auto/Manual	
Emissivity correction	Adjustable from 0.01 to 1.0 or selected from list of materials	
Background temperature correction	Auto	
Atmospheric transmissivity correction	Auto	

www.ulirvision.com

Setting function	Date/time, temperature unit □/□/□K, language	
Languages	10 languages(English, French, Italian, German, Spanish, Portuguese, Russian, Korean, Japanese, Simplified Chinese & Traditional Chinese)	
Image Storage		
Storage type	Built-in flash, >700 images	Built-in flash card, up to >500 images
	8G SD card, up to >11200 images	8G SD card, up to >8000 images
Signal frame infrared image format	JPEG, with 14-Bit radiometric image	
Voice annotation	40s voice record, stored with per image via built-in microphone	
Laser Point		
Grade/Type	Class 2, 1mW/635nmRed	
Interfaces		
Power interface	Yes	
SD card slot	Yes	
Video output	CVBS	
Audio output	Yes	
USB	USE2.0, radiometric images、 measurement data and voice are transferred to PC	
Tripod	1/4" -20	
Power System		
Battery type	Lithium battery	
Battery operation time	2h continuous	
External power	DC: 5V±5%	
Charging system	Intelligent charger or in camera	
Power saving	Yes	
Environment Parameters		
Operating temperature range	-20℃ ~ +50℃	
Storage temperature range	-40℃ ~ +70℃	
Humidity	≤95%(Non-condense)	
Vibration	2G(IEC60068-2-6)	
Shock	25G(IEC60068-2-29)	
Encapsulation	IP54(IEC60529)	
Physical Data		
Size	128mm×62mm×154mm	
Weight	≤0.4kg(with battery and standard lens)	
Packing		

ULIRVISION



Standard	Thermal imaging camera with standard IR lens, 2 Li-ion batteries, battery charger, adapter, USB cable, SD card, SD card reader, USB flash drive, warranty card, calibration book, carrying case, user manual
----------	--



فن آوران مادون قرمز (سهامی خاص)
Fanavaran Madoon Ghermez Pvt.J.S

تهران، بلوار کریمخان زند، شماره ۱۰۳، واحد ۴، کد پستی: ۱۵۸۵۶۸۳۷۳۵
تلفن: ۸۸۸۱۳۱۱ | فاکس: ۸۸۸۱۳۱۴ | info@fmg-tech.ir | www.fmg-tech.ir
Flat 4, No.103, Karimkhan Zand Ave., Tehran-1585683735, Iran
Tel: +98(21)88813101 | www.ir-tc.com | E-mail: info@ir-tc.com

www.ulirvision.com